M-CHLOROTOLUENE

CAUTIONARY RESPONSE INFORMATION Common Synonyms Pungent 1-Chloro-3-methylbenzene 3-Chloro-1-methylbenzene Sinks in water Keep people away. Avoid contact with liquid and vapor Avoid inhalation. Wear self-contained positive pressure breathing apparatus wear selection clothing. Shut off ignition sources. Call fire department. Notify local heath and pollution control agencies. Combustible Fire Poisonous gases may be produced in fire Containers may explode in fire. Flash back along vapor trail may occur. Vapor may explode if ignited in an enclosed area. Wear self-contained positive pressure breathing apparatus and full protective clothing. Extinguish small fires: dry chemical, CO₂, water spray or foam; large fires: water spray, fog or foam. CALL FOR MEDICAL AID. **Exposure** WAPUK May be harmful if inhaled or absorbed through the skin. Irritating to eyes, skin, nose and throat. Move to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen. Harmful if swallowed or absorbed through skin. rarmul if swainowed or absorbed through skin. Irritating to skin and eyes. IF IN EYES OR ON SKIN, flush with running water for at least 15 min.; hold eyelids open if necessary. Remove and isolate contaminated clothing and shoes at IF SWALLOWED and victim is CONSCIOUS, have victim drink water or milk. DO NOT INDUCE VOMITING. IF SWALLOWED and victim is UNCONSCIOUS OR HAVING CONVULSIONS, do nothing except keep victim warm. Effect of low concentrations on aquatic life is unknown. Water

1. CORRECTIVE RESPONSE ACTIONS

Pollution

Stop discharge Contain undissolved material Dilute and disperse dissolved material Collection Systems: Pump; Dredge Chemical and Physical Treatment: Absorb

2. CHEMICAL DESIGNATIONS

- CG Compatibility Group: 36; Halogenated hydrocarbons
 2.2 Formula: CIC₆H₄CH₃
- Formula: CIC6H-GHs
 IMO/UN Designation: 3.3/2238
 DOT ID No.: 2238
 CAS Registry No.: 108-41-8
 NAERG Guide No.: 130
 Standard Industrial Trade Classification:

- 51139

3. HEALTH HAZARDS

May be dangerous if it enters water intakes Notify local health and wildlife officials.

Notify operators of nearby water intakes

- 3.1 Personal Protective Equipment: Wear self-contained positive pressure breathing apparatus and full protective clothing.
- protoms Following Exposure: Inhalation causes upper respiratory irritation. Irritating to skin and eyes. May be absorbed through the skin. Prolonged exposure may result in systemic toxic effects. Harmful if swallowed.
- 3.3 Treatment of Exposure: INHALATION: Move to fresh air. If not breathing, give artificial respiration, If breathing is difficult, give oxygen. EYES OR SKIN: Flush with running water for at least 15 min.; hold eyelids open if necessary. Remove and isolate contaminated clothing and shoes at the site. INGESTION: If victim is conscious, have victim drink water or milk. DO NOT INDUCE VOMITING. If victim is UNCONSCIOUS OR HAVING CONVULSIONS, do nothing except keep victim warm.
- 3.4 TLV-TWA: Not listed. 3.5 TLV-STEL: Not listed.
- 3.6 TLV-Ceiling: Not listed.
- 3.7 Toxicity by Ingestion: Currently not available3.8 Toxicity by Inhalation: Currently not available.
- 3.9 Chronic Toxicity: Prolonged and repeated vapor exposure may result in systemic toxic effects.
 3.10 Vapor (Gas) Irritant Characteristics: Vapors are moderately irritating such that personnel will not
- usually tolerate moderate or high concentrations.

 3.11 Liquid or Solid Characteristics: Minimum hazard. If spilled on clothing and allowed to remain, may
- cause smarting and reddening of skin.
- 3.12 Odor Threshold: Currently not available
- 3.13 IDLH Value: Not listed.
- 3.14 OSHA PEL-TWA: Not listed. 3.15 OSHA PEL-STEL: Not listed.
- 3.16 OSHA PEL-Ceiling: Not listed.
- 3.17 EPA AEGL: Not listed

4. FIRE HAZARDS

- 4.1 Flash Point: 123°F. C.C.
- 4.2 Flammable Limits in Air: 1.36% (LFL)
- 4.3 Fire Extinguishing Agents: Small fires: dry chemical, CO₂, water spray or foam; large fires: water spray, fog or foam.
- 4.4 Fire Extinguishing Agents Not to Be Used: Not pertinent
- Special Hazards of Combustion
 Products: May contain toxic chloride
- 4.6 Behavior in Fire: May produce toxic and
- irritating chloride fumes 4.7 Auto Ignition Temperature: Currently not
- 4.8 Electrical Hazards: Currently not available
- 4.9 Burning Rate: Currently not available
- 4.10 Adiabatic Flame Temperature: Currently not available
- 4.11 Stoichometric Air to Fuel Ratio: 40.5 (calc.)
- 4.12 Flame Temperature: Currently not available
- 4.13 Combustion Molar Ratio (Reactant to Product): 11.0 (calc.)
- 4.14 Minimum Oxygen Concentration for Combustion (MOCC): Not listed

5. CHEMICAL REACTIVITY

- 5.1 Reactivity with Water: No reaction
- 5.2 Reactivity with Common Materials: Currently not available
- 5.3 Stability During Transport: Stable
- 5.4 Neutralizing Agents for Acids and Caustics: Not pertinent
- 5.5 Polymerization: Not pertinent
- 5.6 Inhibitor of Polymerization: Not pertinent

6. WATER POLLUTION

- 6.1 Aquatic Toxicity:
- 18 ppm/7d/guppy LD∞/fresh water 6.2 Waterfowl Toxicity: Currently not
- 6.3 Biological Oxygen Demand (BOD): Currently not available
- Food Chain Concentration Potential:
- Currently not available GESAMP Hazard Profile:
- Bioaccumulation: Z Damage to living resources: 2 Human Oral hazard: (1) Human Contact hazard: | Reduction of amenities: X

7. SHIPPING INFORMATION

- 7.1 Grades of Purity: Currently not available
- 7.2 Storage Temperature: Ambient
- 7.3 Inert Atmosphere: Not listed
- 7.4 Venting: Not pertinent
- 7.5 IMO Pollution Category: B
- 7.6 Ship Type: 3
- 7.7 Barge Hull Type: Currently not available

8. HAZARD CLASSIFICATIONS

- 8.1 49 CFR Category: Flammable liquid
- 8.2 49 CFR Class: 3
- 8.3 49 CFR Package Group: III 8.4 Marine Pollutant: Yes
- 8.5 NFPA Hazard Classification:
 - Category Classification Health Hazard (Blue)........ 2 Flammability (Red)..... 2 Instability (Yellow).....
- 8.6 EPA Reportable Quantity: Not listed.
- 8.7 EPA Pollution Category: Not listed.
- 8.8 RCRA Waste Number: Not listed
- 8.9 EPA FWPCA List: Not listed

9. PHYSICAL & CHEMICAL **PROPERTIES**

- 9.1 Physical State at 15° C and 1 atm: Liquid
- 9.2 Molecular Weight: 126.59
- 9.3 Boiling Point at 1 atm: 323.6°F = 162°C = 435.2°K
- 9.4 Freezing Point: -54°F = -47.8°C = 225.4°K
- 9.5 Critical Temperature: 730°F = 388°C = 161°K (est.)
- 9.6 Critical Pressure: 567 psia = 38.6 atm = 3.91 MN/m2 (est.)
- 9.7 Specific Gravity: 1.0722 at 20°C
- 9.8 Liquid Surface Tension: Currently not
- 9.9 Liquid Water Interfacial Tension: Currently not available
- 9.10 Vapor (Gas) Specific Gravity: 4.4
- 9.11 Ratio of Specific Heats of Vapor (Gas): Currently not available
- **9.12 Latent Heat of Vaporization:** 143 Btu/lb = 79.6 cal/g = 3.3 X 10⁵ J/kg
- 9.13 Heat of Combustion: Currently not available
- 9.14 Heat of Decomposition: Not pertinent
- 9.15 Heat of Solution: Currently not available
- 9.16 Heat of Polymerization: Not pertinent
- 9.17 Heat of Fusion: Currently not available 9.18 Limiting Value: Currently not available
- 9.19 Reid Vapor Pressure: Currently not available

M-CHLOROTOLUENE

9.20 SATURATED LIQUID DENSITY		9.21 LIQUID HEAT CAPACITY		9.22 LIQUID THERMAL CONDUCTIVITY		9.23 LIQUID VISCOSITY	
Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F	Temperature (degrees F)	British thermal unit inch per hour-square foot-F	Temperature (degrees F)	Centipoise
68	66.930		CURRENTLY NOT AVAILABLE		CURRENTLY NOT AVAILABLE		CURRENTLY NOT AVAILABLE

9.24 SOLUBILITY IN WATER		9.25 SATURATED VAPOR PRESSURE		9.26 SATURATED VAPOR DENSITY		9.27 IDEAL GAS HEAT CAPACITY	
Temperature (degrees F)	Pounds per 100 pounds of water	Temperature (degrees F)	Pounds per square inch	Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F
	I NSOLUBLE	50 75 100 125 150 175 200 225 250 275 300	0.020 0.077 0.197 0.409 0.744 1.233 1.910 2.809 3.967 5.422 7.210	50 75 100 125 125 175 200 225 250 275 300	0.00049 0.00169 0.00407 0.00803 0.01400 0.02239 0.03363 0.04815 0.06637 0.08874 0.11568		CURRENTLY NOT AVAILABLE