OILS, MISCELLANEOUS: LUBRICATING

CAUTIONARY RESPONSE INFORMATION Common Synonyms Crankcase oil Motor oil Transmission oil Floats on water Call fire department. Avoid contact with liquid Notify local health and pollution control agencies. Combustible Conidustribe: Extinguish with dry chemical, foam or carbon dioxide. Water may be ineffective on fire. Cool exposed containers with water. CALL FOR MEDICAL AID. **Exposure** LIQUID Irritating to skin and eyes. Harmful if swallowed. Remove contaminated clothing and shoes. Flush affected areas with plenty of water. IF IN EYES, hold eyelids open and flush with plenty of water. IF SWALLOWED and victim is CONSCIOUS, have victim drink water DO NOT INDUCE VOMITING. Effect of low concentrations on aquatic life is unknown. Water Fouling to shoreline. May be dangerous if it enters water intakes. **Pollution** Notify local health and wildlife officials. Notify operators of nearby water intakes

1.	CORRECTIVE	RESPONSE	ACTIONS

Stop discharge Collection Systems: Skim Chemical and Physical Treatment: Absorb Clean shore line Salvage waterfowl

2. CHEMICAL DESIGNATIONS

- CHEMICAL DESIGNAITIONS
 CG Compatibility Group: 33;
 Miscellaneous Hydrocarbon Mixtures
 Formula: Not applicable
 IMO/UN Designation: 3.3/1270
 DOT ID No.: 1288
 CAS Registry No.: Currently not available
 NAERG Guide No.: 128
 Standard Industrial Trade Classification:
 33450

3. HEALTH HAZARDS

- 3.1 Personal Protective Equipment: Protective gloves; goggles or face shield.
- 3.2 Symptoms Following Exposure: INGESTION: minimal gastrointestinal tract irritation; increased frequency of bowel passage may occur. ASPIRATION: pulmonary irritation is normally minimal but may become more severe several hours after exposure.
- Treatment of Exposure: INGESTION: do NOT lavage or induce vomiting. ASPIRATION: treatment probably not required; delayed development of pulmonary irritation can be detected by serial chest x-rays. EYES: wash with copious quantity of water. SKIN: wipe off and wash with soap and
- 3.4 TLV-TWA: Not listed.
- 3.5 TLV-STEL: Not listed
- 3.6 TLV-Ceiling: Not listed.
- 3.7 Toxicity by Ingestion: Grade 1; LD₅₀ = 5 to 15 g/kg
 3.8 Toxicity by Inhalation: Currently not available.
- 3.9 Chronic Toxicity: Currently not available
- 3.10 Vapor (Gas) Irritant Characteristics: Vapors cause a slight smarting of the eyes or respiratory system if present in high concentrations. The effect is temporary.
- 3.11 Liquid or Solid Characteristics: Minimum hazard. If spilled on clothing and allowed to remain, may cause smarting and reddening of the skin.
- 3.12 Odor Threshold: Currently not available
- 3.13 IDLH Value: Not listed.
- 3.14 OSHA PEL-TWA: Not listed.
 3.15 OSHA PEL-STEL: Not listed.
- 3.16 OSHA PEL-Ceiling: Not listed.
- 3.17 EPA AEGL: Not listed

4. FIRE HAZARDS

- 4.1 Flash Point: 300°F C.C.
- **4.2 Flammable Limits in Air:** Currently not available
- **4.3 Fire Extinguishing Agents:** Dry chemical, foam, or carbon dioxide
- **4.4 Fire Extinguishing Agents Not to Be Used:** Water of foam may cause frothing.
- Special Hazards of Combustion Products: Not pertinent
- 4.6 Behavior in Fire: Not pertinent
- 4.7 Auto Ignition Temperature: 500°F-700°F
- 4.8 Electrical Hazards: Not pertinent
- 4.9 Burning Rate: 4 mm/min
- 4.10 Adiabatic Flame Temperature: Currently not available
- 4.11 Stoichometric Air to Fuel Ratio: Not pertinent.
- 4.12 Flame Temperature: Currently not
- 4.13 Combustion Molar Ratio (Reactant to Product): Not pertinent
- 4.14 Minimum Oxygen Concentration for Combustion (MOCC): Not listed

5. CHEMICAL REACTIVITY

- 5.1 Reactivity with Water: No reaction
- 5.2 Reactivity with Common Materials: No reaction
- 5.3 Stability During Transport: Stable
- 5.4 Neutralizing Agents for Acids and Caustics: Not pertinent
- 5.5 Polymerization: Not pertinent
- 5.6 Inhibitor of Polymerization: Not pertinent

6. WATER POLLUTION

- 6.1 Aquatic Toxicity: Currently not available
- 6.2 Waterfowl Toxicity: Currently not
- 6.3 Biological Oxygen Demand (BOD):
- Currently not available 6.4 Food Chain Concentration Potential:
- 6.5 GESAMP Hazard Profile: Not listed

7. SHIPPING INFORMATION

- 7.1 Grades of Purity: Various viscosities
- 7.2 Storage Temperature: Ambient
- 7.3 Inert Atmosphere: No requirement
- 7.4 Venting: Open (flame arrester)
- 7.5 IMO Pollution Category: Currently not available
- 7.6 Ship Type: Currently not available
- 7.7 Barge Hull Type: Currently not available

8. HAZARD CLASSIFICATIONS

- 8.1 49 CFR Category: Flammable liquid 8.2 49 CFR Class: 3
- 8.3 49 CFR Package Group: III
- 8.4 Marine Pollutant: No
- 8.5 NFPA Hazard Classification:

Category Classification Health Hazard (Blue)....... 0 Flammability (Red)..... Instability (Yellow).....

- 8.6 EPA Reportable Quantity: Not listed.
- 8.7 EPA Pollution Category: Not listed.
- 8.8 RCRA Waste Number: Not listed
- 8.9 EPA FWPCA List: Not listed

9. PHYSICAL & CHEMICAL **PROPERTIES**

9.1 Physical State at 15° C and 1 atm: Liquid

- 9.2 Molecular Weight: Not pertinent
- 9.3 Boiling Point at 1 atm: Very high
- 9.4 Freezing Point: Not pertinent
- 9.5 Critical Temperature: Not pertinent
- 9.6 Critical Pressure: Not pertinent
- 9.7 Specific Gravity: (est.) 0.902 at 20°C (liquid)
- 9.8 Liquid Surface Tension: 36-37.5 dynes/cm =
- 0.036-0.0375 N/m at 20°C 9.9 Liquid Water Interfacial Tension: 33-54 dynes/cm = 0.033-0.054 N/m at 20°C
- 9.10 Vapor (Gas) Specific Gravity: Not pertinent
- 9.11 Ratio of Specific Heats of Vapor (Gas): Not pertinent 9.12 Latent Heat of Vaporization: Not pertinent
- 9.13 Heat of Combustion: -18.486 Btu/lb =
- -10,270 cal/g = -429.98 X 10⁵ J/kg
- 9.14 Heat of Decomposition: Not pertinent
- 9.15 Heat of Solution: Not pertinent 9.16 Heat of Polymerization: Not pertinent
- 9.17 Heat of Fusion: Currently not available
- 9.18 Limiting Value: Currently not available 9.19 Reid Vapor Pressure: Currently not

NOTES

OILS, MISCELLANEOUS: LUBRICATING

9.20 SATURATED LIQUID DENSITY		9.21 LIQUID HEAT CAPACITY		9.22 LIQUID THERMAL CONDUCTIVITY		9.23 LIQUID VISCOSITY	
Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F	Temperature (degrees F)	British thermal unit inch per hour-square foot-F	Temperature (degrees F)	Centipoise
50 52 54 56 68 60 64 66 68 70 72 74 76 78 80 82 84	56.180 56.180 56.180 56.180 56.180 56.180 56.180 56.180 56.180 56.180 56.180 56.180 56.180 56.180	50 52 54 56 60 62 64 66 68 70 72 74 78 80 82 84 86 88 90 92 94 98	0.460 0.461 0.462 0.463 0.464 0.465 0.466 0.467 0.468 0.469 0.470 0.471 0.472 0.473 0.475 0.476 0.477 0.478 0.479 0.480 0.481 0.482 0.483 0.484 0.485	35 40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120	0.920 0.919 0.918 0.917 0.916 0.915 0.913 0.912 0.911 0.910 0.908 0.908 0.908 0.907	100	275.000

9.24 SOLUBILITY IN WATER		9.25 SATURATED VAPOR PRESSURE		9.26 SATURATED VAPOR DENSITY		9.27 IDEAL GAS HEAT CAPACITY	
Temperature (degrees F)	Pounds per 100 pounds of water	Temperature (degrees F)	Pounds per square inch	Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F
	I NSOLUBLE	70 75 80 85 90 95 100 115 115 125 130 135 140 145 150 160 165 170 175 180 185	0.042 0.049 0.057 0.065 0.076 0.087 0.100 0.114 0.131 0.149 0.170 0.193 0.218 0.247 0.279 0.314 0.352 0.395 0.443 0.495 0.552 0.615 0.683 0.758 0.841 0.930		NOT PERTINENT		NOT PERTINENT